Applicant: Tatsuya Yoshikawa Attorney's Docket No.: 13298-004001 / F 2001-43-US

Serial No.: 09/888,009 Filed: June 22, 2001

Page : 2 of 6

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

Listing of Claims:

- (Currently Amended) An exhaust gas purifying catalyst comprising:
 a composition including a first <u>catalytic</u> component of a composite oxide containing
 zirconium and manganese and/or cobalt and a second <u>catalytic</u> component of zeolite;
 wherein the zeolite is a proton zeolite or is modified with at least one element selected from the
 group consisting of cerium, lanthanum, phosphorus, boron, gallium, magnesium, and mixtures
 thereof.
- 2. (Previously Presented) A catalyst according to claim 1, wherein the composite oxide and the zeolite are in the state of a physical mixture.
- 3. (Previously Presented) A catalyst according to claim 1, wherein the first and second components are deposited on a monolithic carrier as a homogeneous physical mixture or as separated layers.
- 4. (Original) A catalyst according to claim 1, wherein a weight ratio of the manganese and/or the cobalt to the zirconium comprise from 1 to 50 weight parts as oxide per 100 weight parts of the zirconium oxide.
- 5. (Original) A catalyst according to claim 4,wherein the weight ratio of the manganese and/or the cobalt to the zirconium comprise from 5 to 40 weight parts as oxide per 100 weight parts of the zirconium oxide.

Applicant: Tatsuya Yoshikawa Attorney's Docket No.: 13298-004001 / F 2001-43-US

Serial No.: 09/888,009 Filed: June 22, 2001

Page : 3 of 6

6. (Original) A catalyst according to claim 1, wherein a first component/second component ratio is in the range of 0.05 to 2.0: 1 by weight.

- 7. (Original) A catalyst according to claim 6, wherein the first component/second component ratio is in the range of 0.1 to 0.7: 1 by weight.
- 8. (Original) A catalyst according to claim 1, wherein the first component has the manganese and/or cobalt deposited on the zirconium oxide.
- 9. (Original) A catalyst according to claim 1, wherein the first component is further deposited on a refractory inorganic substance.
- 10. (Original) A catalyst according to claim 1, wherein the second component is a proton zeolite.
- 11. (Original) A catalyst according to claim 10, wherein the zeolite is at least one member selected from the group consisting of ZSM-5, Ferrierite, Faujasite, β-zeolite, Mordenite and mixtures thereof.
- 12. (Previously Presented) A catalyst according to claim 1, wherein the second component is a zeolite modified with at least one element selected from the group consisting of cerium, lanthanum, phosphorus, boron, gallium, magnesium, and mixtures thereof.
- 13. (Original) A catalyst according to claim 1, wherein the first component further contains at least one element selected from the group consisting of bismuth, iron, cerium, praseodymium, gadolinium, lanthanum, barium, strontium, calcium, cesium, yttrium and mixtures thereof.

Applicant: Tatsuya Yoshikawa Attorney's Docket No.: 13298-004001 / F 2001-43-US

Serial No.: 09/888,009 Filed: June 22, 2001

Page : 4 of 6

14. (Original) A catalyst according to claim 13, wherein an amount of the element comprise from 0.2 to 50 weight percent based on the weight of the manganese and/or the cobalt, as reduced to weight of the metal.

- 15. (Original) A catalyst according to claim 14, wherein an amount of the element comprise from 1 to 40 weight percent based on the weight of the manganese and/or the cobalt, as reduced to weight of the metal.
- 16. (Currently Amended) A method for purifying NO_X in an exhaust gas by using a catalyst, catalyst comprising: a composition comprising a first <u>catalytic</u> component of composite oxide containing zirconium and manganese and/or cobalt and a second <u>catalytic</u> component of zeolite in the state of a physical mixture;

wherein the zeolite is a proton zeolite or is modified with at least one element selected from the group consisting of cerium, lanthanum, phosphorus, boron, gallium, magnesium, and a mixture thereof.

- 17. (Original) A method according to claim 16, wherein the exhaust gas is from a diesel engine or lean burn engine.
- 18. (Previously Presented) A catalyst according to claim 1, wherein the zeolite is partly modified with at least one element selected from the group consisting of cerium, lanthanum, phosphorus, boron, gallium, magnesium, and mixtures thereof.
- 19. (New) A catalyst according to claim 1, wherein the zeolite is modified with at least one element selected from the group consisting of cerium, lanthanum, gallium, magnesium, and mixtures thereof.
- 20. (New) A catalyst according to claim 13, wherein the zeolite is modified with at least one element selected from the group consisting of cerium, lanthanum, gallium, magnesium, and mixtures thereof.